


Denim and sanforized fabrics

Dollfus & Muller
The manufacturer of Felt Blankets
is approved by
THE SANFORIZED COMPANY
for all shrinkage machines

Thank you for celebrating
our 200th Anniversary in 2011 with us !



- Best drying
- Excellent handle
- Controlled shrinkage

DOZZFUS MULLER

TECHNOLOGY FOR FASHION

Since 1811

Spare parts for Sanforizing machines

Our high quality products are specially recommended for the following Sanforizing machines : MONFORTS, MORRISON, BRÜCKNER, DHALL, CIBITEX, MUZZI, TEPA, SPEROTTO, RONSON, SWASTIK, POONG KWANG, BISIO, DAROITEX, PAGANINI, ...

ENDLESS FELTS FOR THE PALMER UNIT

Tension applied on the felt	Resistance to chemical products	Description	Quality	Characteristics				
				Fibres composition	Maximum working T°	Thickness (in mm)	Weight (g/m ²)	Air Flow (CFM : Cubic Feet / min under 124 Pa)
Pneumatic	+++	Recommended for Denim finishing	SYPOR 200 TK	100% Aramid	190°C 370°F	7	2000	12
	++	Original quality	SYPOR 200	30% Acrylic / 70% Polyester	160°C 320°F	6	2000	10
	++	Reinforced quality	SYPOR 240			7	2400	8
	+	Recommended for the finishing of some sensitive fabrics	SYPOR SLS 200	50% Wool / 50% Polyester	6	2000	11	
Mechanical with weights	+++	Reinforced quality recommended for Denim finishing	SYPOR 233 TK	100% Aramid	190°C 370°F	7	2300	11
	++	Reinforced quality	SYPOR 233	30% Acrylic / 70% Polyester	160°C 320°F	7	2300	8

+ Medium ++ Strong +++ Very High

STEAMING CYLINDER FABRICS, RUBBER BELT, FELT PADS AND ROLL COVERING

Product	Description	Quality	Characteristics		
			Composition	Thickness (in mm)	Weight (g/m ²)
Steaming cylinder fabrics or felts	Original woven quality	DASZ	100% Polyester	0.1	240
	High steam resistant woven quality	HZ 23	100% Nomex® (Aramid)	0.2	210
	High steam resistant felted quality	HZ 40	100% Nomex® (Aramid) fibres	2.5	390
Rubber belt	Compressive belt	Rubber belt	Rubber	67 (between 50 to 72)	76000
Felt pads	Cooling of the rubber belt in the shrinking unit	RAC 200	30% Acrylic / 70% Polyester	6	2000
	Cleaning of the Palmer heating drum	L 200 - 300	100% Wool	8	2000 - 3000
Roll Covering	Covering the guiding cylinder of the palmer unit	DM 3	Synthetic rubber	1.8	1600



Steam fabric



Rubber belt



Palmer felt



Felt pad



Roll covering

