

NP - EM - PLG

zone 1

zone 2

II 2GD Exdb IIC Gb Ex tb IIIC Db



zone 21

zone 22

II 2GD Exeb IIC Gb Ex tb IIIC Db



RACCORDI ED ACCESSORI

FITTING AND ACCESSORY



IP66 / IP67

Diametro Diameter	Diametro Diameter	Acc. Zinc. steel	Ottone Brass	SS316 SS316
1/2"	M20	NP 1G	NP 1B	NP 1S
3/4"	M25	NP 2G	NP 2B	NP 2S
1 "	M32	NP 3G	NP 3B	NP 3S
1 1/4"	M40	NP 4G	NP 4B	NP 4S
1 1/2"	M50	NP 5G	NP 5B	NP 5S
2 "	M63	NP 6G	NP 6B	NP 6S
2 1/2"	M75	NP 7G	NP 7B	NP 7S
3 "	M90	NP 8G	NP 8B	NP 8S
4 "	M100	NP 10G	NP 10B	NP 10S

I Nippli consentono il Collegamento tra imbrocchi femmina.

Nipples allow connections between female mouthpieces.

Filettature-Threads: ISO 7/1 (BSPT) - NPT
METRIC - ISO 228 (BSPP)

Materiali-Materials: Acciaio zincato - *Mild steel zinc plated*
Acciaio inox - *Stainless steel*
Ottone nickelato - *Brass Nickel plated*



Diametro Diameter	Diametro Diameter	Acc. Zinc. steel	Ottone Brass	SS316 SS316
1/2"	M20	EM 1G	EM 1B	EM 1S
3/4"	M25	EM 2G	EM 2B	EM 2S
1 "	M32	EM 3G	EM 3B	EM 3S
1 1/4"	M40	EM 4G	EM 4B	EM 4S
1 1/2"	M50	EM 5G	EM 5B	EM 5S
2 "	M63	EM 6G	EM 6B	EM 6S
2 1/2"	M75	EM 7G	EM 7B	EM 7S
3 "	M90	EM 8G	EM 8B	EM 8S
4 "	M100	EM 10G	EM 10B	EM 10S

I Manicotti consentono il collegamento tra estremità filettate maschio.

Couplings allow connections between male threaded ends.

Filettature-Threads: ISO 7/1 (BSPT) - NPT
METRIC - ISO 228 (BSPP)

Materiali-Materials: Acciaio zincato - *Mild steel zinc plated*
Acciaio inox - *Stainless steel*
Ottone nickelato - *Brass Nickel plated*



Diametro Diameter	Diametro Diameter	Alluminio Aluminium	Ottone Brass	SS316 SS316
1/2"	M20	ELF 1A	ELF 1B	ELF 1S
3/4"	M25	ELF 2A	ELF 2B	ELF 2S
1 "	M32	ELF 3A	ELF 3B	ELF 3S
1 1/4"	M40	ELF 4A	ELF 4B	ELF 4S
1 1/2"	M50	ELF 5A	ELF 5B	ELF 5S
2 "	M63	ELF 6A	ELF 6B	ELF 6S
2 1/2"	M75	ELF 7A	ELF 7B	ELF 7S
3 "	M90	ELF 8A	ELF 8B	ELF 8S
4 "	M100	ELF 10A	ELF 10B	ELF 10S

Curve a gomito non ispezionabili

Closed Bends

Filettature-Threads: ISO 7/1 (BSPT) - NPT
METRIC - ISO 228 (BSPP)

Materiali-Materials: Alluminio - *Aluminium*
Acciaio inox - *Stainless steel*
Ottone nickelato - *Brass Nickel plated*



Diametro Diameter	Diametro Diameter	Acc. Zinc. steel	Alluminio Aluminium	Ottone Brass	SS316 SS316
1/2"	M20	PLG1G	PLG1A	PLG1B	PLG1S
3/4"	M25	PLG2G	PLG2A	PLG2B	PLG2S
1 "	M32	PLG3G	PLG3A	PLG3B	PLG3S
1 1/4"	M40	PLG4G	PLG4A	PLG4B	PLG4S
1 1/2"	M50	PLG5G	PLG5A	PLG5B	PLG5S
2 "	M63	PLG6G	PLG6A	PLG6B	PLG6S
2 1/2"	M75	PLG7G	PLG7A	PLG7B	PLG7S
3 "	M90	PLG8G	PLG8A	PLG8B	PLG8S
4 "	M100	PLG10G	PLG10A	PLG10B	PLG10S

I Tappi PLG permettono la chiusura di imbrocchi femmina o di fori inutilizzati.

Plugs PLG are closing off female mouthpieces or unused openings.

Filettature-Threads: ISO 7/1 (BSPT) - NPT
METRIC - ISO 228 (BSPP)

Materiali-Materials: Alluminio - *Aluminium*
Acciaio inox - *Stainless steel*
Ottone nickelato - *Brass Nickel plated*
Acciaio zincato - *Mild steel zinc plated*

