



INDUSTRIAL RACKMOUNT Q87AX4-26 4U

Here is a great 4U server that can allow you to take full advantage of the extensive expansions slots found on Corvalent motherboards. This system makes use of our powerful Q87AX motherboard, powered by the Intel® i7™ family of processors. This system gives you plenty of horsepower, storage, and expandability to tackle almost any task. From high end imaging applications, to machine control or simulation systems, this design gives you the features you need to get the job done.




PRODUCT HIGHLIGHTS

- 4U Rack Mount Chassis
- Embedded Haswell 4th Gen
- Four (4) DIMM sockets; Max memory 32GB DDR3
- Six (6) powered SATA III connectors
- Huge range of expansion options
- 4 x DIMM sockets; Max memory 32GB DDR3
- Up to twelve (12) USB ports
- Operating Temperature: 0°C to 40°C
- 7 to Ten 10 Year Guaranteed Production



CorSys Q87AX4-2I 4U

Industrial Racmount



TECHNICAL SPECIFICATIONS

System

Microprocessor	i7-4790S i5-4590T i5-4590S i3-4350T i3-4360 i3-4340TE i7-4770S i7-4770TE i5-4570S i5-4570TE i3-4330TE i3-4330 Xeon E3-1225 Xeon E3-1268L Xeon E3-1275
Chipset	Intel® Q87
Motherboard	Q87AX
System Bus	1 x PCIe x16 (Gen. 3.0) 1 x PCIe x4 slot (Gen. 3.0) 1 x PCIe x1 slot (Gen. 3.0) 4 x PCI slots 1 x MiniPCIe slot with mSATA support
System Memory	DDR3 (1066/1333/1600 MHz) Dual channel, 32GB max unbuffered, non-ECC
Audio	Realtek ALC886 HD Audio CODEC, Mic. in, Stereo Line Out and Line In jacks on I/O back-panel 10-pin

Onboard I/O

HD Audio header.
4 x external USB 2.0 ports on rear panel
2 x external USB 3.0 ports on rear panel
2 x internal USB 3.0 on 20-pin header
4 x internal USB 2.0 ports on 10-pin headers
6 x powered SATA III 6Gb/s ports supporting Intel Matrix Storage RAID

Onboard Video

3 x independent display streams via 1x DVI, 1x VGA and 1x DisplayPort on rear panel; Max. resolution up to 3840 x 2160
--

Ethernet

2 x RJ45, Gigabit Ethernet ports (Intel i217LM & 82574L) Industrial Devices
Hardware temperature monitor
CPU temperature monitor
Watch Dog Timer
GPIO
Post Display
AMI® EFI 64Mbit SPI
Flash ROM

BIOS

Enclosure

Form Factor	177.8mm x 482.6mm x 670.6mm (7.0"H x 19"W x
-------------	---

Drive Bays

26.4"D)
1 x external 3.5" bay
6 x 5.25" bays,
1 x internal 3.5"
optional:
2 x 3.5".
The 5.25" bays may be configured for
8 x 3.5" hot swap drives
1 x optical
or
10 x 3.5" hot swap drives, with no optical

Cooling Units

Power supply, + four (4) 92mm center-mounted fans

Temperature

Operating	0°C to 70°C
-----------	-------------

Temperature

Non-Operating	-40°C to 80°C
---------------	---------------

Humidity

non-condensing	5% to 95% @ 40°C
----------------	------------------

Part Number

Q87AX4-26

LONG LIFE VGA OPTIONS

Video Cards

NVIDIA K620
NVIDIA K2200
NVIDIA K4200

