

CDM-800-EN Gateway Router

Advanced VSAT Solutions



Overview

Comtech EF Data's Advanced VSAT Solutions portfolio provides high-performance satellite-based communication solutions for a diverse range of applications, including maritime and offshore communications, mobile backhaul with RAN optimization, IP trunking and backhaul, corporate and enterprise networks, emergency and disaster recovery. Incorporating advanced technologies developed by Comtech EF Data, AHA Products Group, Memotec and Stampede, the solutions provide unmatched performance, industry-leading bandwidth efficiencies and network optimization – while minimizing Total Cost of Ownership.

Designed for use at the hub site, CDM-800-EN receives the optimized DVB-S2 baseband frames from CTOG-250-EN for transmission over the satellite. It also performs AES-128 encryption for transmission security.

Features

- Symbol rate: 1 Msps to 62 Msps
- DVB-S2 Forward Error Correction
 - Modulation: QPSK, 8PSK, 16APSK, 32APSK
 - Adaptive Coding and Modulation (ACM)
 - Variable Coding and Modulation (VCM)
 - Rolloff : 20%, 25%, 35%
- AES-128 Encryption
- Transmit Frequency: 50 to 180 MHz or 950 to 2150 MHz
- Traffic Interfaces: 2 x 10/100/1000Base-T Ethernet
- Management Interface: 10/100Base-T Ethernet for web and SNMP
- Integrated with NetVue Integrated Management System and Vipersat Management System

Typical Users

- Offshore & Maritime
- Mobile Operators
- Telecom Operators
- Enterprise
- Internet Service Providers (ISPs)

Common Applications

- Maritime & Offshore Communications
- Mobile Backhaul with RAN Optimization
- IP Trunking & Internet Access



CDM-800-EN Back Panel

Specifications

Transmit Data Rate	QPSK	0.479 – 108.255 Mbps
	8PSK	1.740 – 160.0 Mbps
	16APSK	2.575 – 160.0 Mbps
	32APSK	3.623 – 160.0 Mbps
Transmit Symbol Rate	QPSK	1 to 62 Msps
	8PSK	1 to 62 Msps
	16APSK	1 to 47 Msps
	32APSK	1 to 37 Msps
FEC	DVB-S2 Encoder Short Frame, Normal frame	
Modulation & FEC	Data Rate Range (Normal FEC frame, pilots on)	
QPSK 1/4	0.479 – 29.672 Mbps	
QPSK 1/3	0.641 – 39.731 Mbps	
QPSK 2/5	0.771 – 47.779 Mbps	
QPSK 1/2	0.965 – 59.850 Mbps	
QPSK 3/5	1.160 – 71.922 Mbps	
QPSK 2/3	1.291 – 80.029 Mbps	
QPSK 3/4	1.452 – 90.029 Mbps	
QPSK 4/5	1.549 – 96.064 Mbps	
QPSK 5/6	1.615 – 100.148 Mbps	
QPSK 8/9	1.724 – 106.914 Mbps	
QPSK 9/10	1.746 – 108.255 Mbps	
8PSK 3/5	1.740 – 107.853 Mbps	
8PSK 2/3	1.936 – 120.011 Mbps	
8PSK 3/4	2.178 – 135.007 Mbps	
8PSK 5/6	2.422 – 150.181 Mbps	
8PSK 8/9	2.586 – 160.000 Mbps	
8PSK 9/10	2.618 – 160.000 Mbps	
16APSK 2/3	2.575 – 121.007 Mbps	
16APSK 3/4	2.896 – 136.127 Mbps	
16APSK 4/5	3.090 – 145.253 Mbps	
16APSK 5/6	3.222 – 151.428 Mbps	
16APSK 8/9	3.440 – 160.000 Mbps	
16APSK 9/10	3.483 – 160.000 Mbps	
32APSK 3/4	3.623 – 134.063 Mbps	
32APSK 4/5	3.866 – 143.051 Mbps	
32APSK 5/6	4.031 – 149.132 Mbps	
32APSK 8/9	4.303 – 159.207 Mbps	
32APSK 9/10	4.357 – 160.000 Mbps	

Modulator Specifications

Operating Frequency	50 to 180 MHz 950 to 2150 MHz (L-Band) 100 Hz frequency resolution
Frequency Stability	± 0.06 ppm (± 6 x 10 ⁻⁶), 0° to 50°C (32° to 122°F)
Scrambling	PL Scrambling (Gold Codes), disabled
Spectral Inversion	Normal or inverted
Transmit Filtering	Per ETSI EN 302-207
Transmit Filter Rolloff (Alpha)	20%, 25% and 35%
Pilot Insertion	User Selectable – on/off
Output Power	-5 to -25 dBm, in 0.1 dB steps (50 – 180 MHz) -5 to -40 dBm, in 0.1 dB steps (950 – 2150 MHz)
Output Power Accuracy	± 1.0 dB over frequency, data rate, modulation type and temperature range of 0 to 50°C
Transmit On/Off Ratio	-60 dBc minimum
Harmonics and Spurious	Better than -60 dBc/4 kHz (typically < 65 dBc/4 kHz) Measured from 1 to 500 MHz (50 - 180 MHz)

Output Phase	Measured from F _o +/- 500 MHz (950 - 2150 MHz)
Noise	< 1° rms double sided, 100 Hz to 1 MHz (minimum of 6 dB better overall than the Intelsat IESS-308/309 requirement)
	dB/Hz Frequency Offset
	-66.0 100 Hz
	-76.0 1 kHz
	-86.0 10 kHz
	-96.0 100 kHz
	Fundamental AC line spurious is -42 dBc or lower
	The sum of all other single sideband spurious, from 0 to 0.75 x symbol rate, is 48 dBc or lower
Impedance	50 Ω /75 Ω (50 – 180 MHz) 50 Ω (950 – 2150 MHz)
Return Loss	15 dB, minimum (50 – 180 MHz) 12 dB, minimum (15 dB typical) (950 – 2150 MHz)
External TX Carrier Off	By TTL 'low' signal
Test Modes	CW, 1/0 pattern, 2 ^N -1 and 2047 patterns

Connectors

70/140 MHz Transmit	BNC (female)
L-Band Transmit	N-type (female)
External Reference	BNC (female)
10/100Base-T Ethernet interface (IEEE 802.3u)	1 x RJ-45
10/100/1000Base-T Ethernet interface (IEEE 802.3ab)	2 x RJ-45
Remote Control / Console Port	9-pin D-sub (male)

Available Options

Option	Type
-48 VDC, Primary Power Supply	Hardware
24 VDC, 90 W @ 50 °C BUC Power Supply	Hardware
48 VDC, 150 W @ 50 °C BUC Power Supply	Hardware
G.703 Clock Extension	FAST

Physical, Power & Environmental

Dimensions (1RU) (height x width x depth)	1.75" x 19.0" x 17.7" (4.4 x 48 x 44.8 cm) approximate
Power Supply	100-240 VAC, 47 Hz-63 Hz IEC 320 input -48 VDC (HW option)
Operating Temperature	0° to 50°C
Storage temperature	-20° to 70°C
Humidity	95% maximum, non-condensing

Regulatory

CE Mark	EN 301 489-1 (ERM) EN55022 (Emissions) EN55024 (Immunity) EN 61000-3-2 EN 61000-3-3 EN60950 (Safety)
FCC	FCC Part 15, Subpart B



2114 West 7th Street, Tempe, Arizona 85281 USA
Voice: +1.480.333.2200 • Fax: +1.480.333.2540 • Email: sales@comtechefdata.com

See all of Comtech EF Data's Patents and Patents Pending at <http://patents.comtechefdata.com>

Comtech EF Data reserves the right to change specifications of products described in this document at any time without notice and without obligation to notify any person of such changes. Information in this document may differ from that published in other Comtech EF Data documents. Refer to the website or contact Customer Service for the latest released product information