

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size: \varnothing 0.9 mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request



4.1 VA - t_a70/B



Code	Primary (50-60Hz)	Secondary ¹	Layout	Output fuses ²
1214S106	230V	6V - 683 mA	Drawing 1	fuse 800 mA
1214S109	230V	9V - 455 mA	Drawing 1	fuse 500 mA
1214S112	230V	12V - 341 mA	Drawing 1	fuse 400 mA
1214S115	230V	15V - 273 mA	Drawing 1	fuse 315 mA
1214S118	230V	18V - 227 mA	Drawing 1	fuse 250 mA
1214S124	230V	24V - 170 mA	Drawing 1	fuse 200 mA
1214S206	230V	2x 6V - 341 mA	Drawing 2	2 fuses 400 mA
1214S209	230V	2x 9V - 227 mA	Drawing 2	2 fuses 250 mA
1214S212	230V	2x 12V - 170 mA	Drawing 2	2 fuses 200 mA
1214S215	230V	2x 15V - 137 mA	Drawing 2	2 fuses 150 mA
1214T106	115V	6V - 683 mA	Drawing 1	fuse 800 mA
1214T109	115V	9V - 455 mA	Drawing 1	fuse 500 mA
1214T112	115V	12V - 341 mA	Drawing 1	fuse 400 mA
1214T115	115V	15V - 273 mA	Drawing 1	fuse 315 mA
1214T118	115V	18V - 227 mA	Drawing 1	fuse 250 mA
1214T124	115V	24V - 170 mA	Drawing 1	fuse 200 mA
1214T206	115V	2x 6V - 341 mA	Drawing 2	2 fuses 400 mA
1214T209	115V	2x 9V - 227 mA	Drawing 2	2 fuses 250 mA
1214T212	115V	2x 12V - 170 mA	Drawing 2	2 fuses 200 mA
1214T215	115V	2x 15V - 137 mA	Drawing 2	2 fuses 150 mA

Dimensions	mm	Drawing 1 (bottom view)	Drawing 2 (bottom view)	Dimensions	.stp file Download
a max	41.5				
b max	35.5				
h max	27.5				
x typ	5.0				
y typ	25.0				

¹ Rated voltage (No load voltage x 1.44).

² See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.