

## UI series U3917 - 24VA

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size:  $\varnothing$  0.9 mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request
- Fixing with 4 self-tapping screws 3x16mm



## 24 VA - $t_a50/B$



Code	Primary (50-60Hz)	Secondary <sup>1</sup>	Output fuses <sup>2</sup>
U3917S06	2x115V	2x 6 V - 2000 mA	2 fuses 2000 mA
U3917S09	2x115V	2x 9 V - 1333 mA	2 fuses 1600 mA
U3917S12	2x115V	2x 12V - 1000 mA	2 fuses 1000 mA
U3917S15	2x115V	2x 15V - 800 mA	2 fuses 800 mA
U3917S18	2x115V	2x 18V - 667 mA	2 fuses 800 mA

Dimensions	mm	Layout (bottom view)	Dimensions	.stp file Download
a max	68.6			
b max	57.7			
h max	31.7			
x typ	5.0			
x1 typ	6.0			
y typ	45.0			
c typ	62.6			
d typ	50.2			

230V / 2xVsec	230V / 2xIsec	115V / 2xVsec	115V / 2xIsec
Primary double voltage Secondary double voltage	Primary double voltage Secondary double current	Primary double current Secondary double voltage	Primary double current Secondary double current

<sup>1</sup> Rated voltage (No load voltage x 1.22).

<sup>2</sup> See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.