

UI series U4817 - 40VA

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size: \varnothing 0.9 mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request
- Fixing with 4 sheet-metal bolt \varnothing 3x12mm



40 VA - t_a50/B



Code	Primary (50-60Hz)	Secondary ¹	Output fuses ²
U4817S06	2x115V	2x 6V - 3,33 A	2 fuses 4 A
U4817S09	2x115V	2x 9V - 2,22 A	2 fuses 2,5 A
U4817S12	2x115V	2x 12V - 1,66 A	2 fuses 2 A
U4817S15	2x115V	2x 15V - 1,33 A	2 fuses 1,6 A
U4817S18	2x115V	2x 18V - 1,11 A	2 fuses 1,25 A

Dimensions	mm	Layout (bottom view)	Dimensions	.stp file Download
a max	84.0			
b max	70.4			
h max	38.8			
x typ	5.0			
x1 typ	7.0			
y typ	52.5			
c typ	75.0			
d typ	60.4			

230V / 2xVsec	230V / 2xIsec	115V / 2xVsec	115V / 2xIsec
Primary double voltage Secondary double voltage	Primary double voltage Secondary double current	Primary double current Secondary double voltage	Primary double current Secondary double current

¹ Rated voltage (No load voltage x 1.18).

² See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.