

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size:  $\varnothing$  0.9 mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request
- Fixing with 4 sheet-metal bolt  $\varnothing$ 3x12mm



## 60 VA - $t_a$ 50/B



Code	Primary (50-60Hz)	Secondary <sup>1</sup>	Output fuses <sup>2</sup>
U4826S06	2x115V	2x 6V – 5,0 A	2 fuses 5,0 A
U4826S09	2x115V	2x 9V - 3,33 A	2 fuses 4,0 A
U4826S12	2x115V	2x 12V - 2,5 A	2 fuses 2,5 A
U4826S15	2x115V	2x 15V – 2,0 A	2 fuses 2,0 A
U4826S18	2x115V	2x 18V – 1,66 A	2 fuses 2,0 A

Dimensions	mm	Layout (bottom view)	Dimensions	.stp file Download
a max	84.0			
b max	70.4			
h max	47.9			
x typ	5.0			
x1 typ	7.0			
y typ	52.5			
c typ	75.0			
d typ	60.4			

230V / 2xVsec	230V / 2xIsec	115V / 2xVsec	115V / 2xIsec
Primary double voltage Secondary double voltage	Primary double voltage Secondary double current	Primary double current Secondary double voltage	Primary double current Secondary double current

<sup>1</sup> Rated voltage (No load voltage x 1.14).

<sup>2</sup> See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.