


TECHNICAL DATA:

- **Internal parts:** stainless steel
- **Seals:** NBR, FPM
- **Fluid temperature:**
-10°C to +90°C (NBR);
+130°C (FPM)
- **Ambient temperature:** max +55°C
- **Viscosity:** max 21 mm²/s
- **Response time:** 30 - 60 ms
- **Voltage:** standard 12, 24 V DC,
others on request
- **Duty cycle:** continuous (ED100%)
- **Cycling rate:** max 1000 cycles/min
- **Electrical protection:** IP65
IP65 (with plug to ISO 4400)
Long term use in humid environment requires
the use of sealing sets.

Closed when de-energised (NC)



Ports	Orifice size [mm]	Kv (water at 1bar) [l/min]	Differential pressure [bar]		Body	Mass [kg]	Coil type	Model	Order code	Fig.
			min	max						
G3/8	13	28	0	2	Brass	0.79	TM35	D329	331762	1
G3/8	13	28	0	0.3	Brass	0.79	TM35	D329	331763	1
G1/2	17	60	0	1	Brass	0.79	TM35	D329	331773	2
G3/4	22	105	0	0.2	Brass	1.75	TM40	D327	331748	2
	22	105	0	2	Brass	1.75	TM40	XD327	331750	

OPTIONS:

- EEx me II explosionproof coils
- INOX body
- NPT ports
- Other versions on request.