



KEY FEATURES

- Fiber Laser Welders from 2 kW 5 kW
- Optional two-way time-share contributes to improvement in productivity
- Enables the use of accurate 200 micron fiber cores to achieve a high energy concentration for welding difficult metals at high speed
- High-efficiency fiber laser saves power consumption
- Easy operation via touch screen
- Program pulse shaping, modulation control and monitor operation status without the need for an external PC
- Error details, power monitor status and I/O monitoring shown on a built-in screen
- Standard safety shutter by beam switch method
- Long-life laser diodes provide high reliability and improves maintenance cost

ML-69 B Series

High Power Fiber Laser Welders

The ML-69 B Series are high-power fiber laser welders with a maximum output of 5 kW. High power laser enables welding of even thick plates at a high speed.

One compact, proven industrial package with the Miyachi worldwide support makes it an ideal production tool. The integrated back reflection measurement safeguard the laser in all circumstances against damage due to back reflection.

The good beam quality of the fiber lasers coupled with high CW (Continuous Wave) powers offers deep penetration welding at high speeds. These fiber lasers replace not only traditional CO2 laser and Disk lasers, but also MIG, TIG and electron beam welding.

The ML-69 B Series have the advantage of excellent laser oscillation efficiency, energy saving and low cost of ownership, resulting in contributing to environmentally-friendly manufacturing. The integrated power measurement and active regulation provides exceptional stability of the pulse energy (typical <0,5% pulse to pulse).

TYPICAL APPLICATIONS


The ML-69 B Series performs high-speed CW welding and welding of precision metal plates. Typical applications are welding of electronic components, automotive parts, mechanical parts, plastic parts, medical equipment and precision sheet metals; sealing of minute parts; fine spot welding; high-speed seam welding; thick plate welding; etc.



Fiber laser welding of stainless steel



Fiber laser welding of gear parts




Turbocharger components



MIYACHI

ML-69 B SERIES BEAM QUALITY

The ML-69 B Series performs high-speed CW welding and welding of precision metal plates. Typical applications are welding of electronic components, automotive parts, mechanical parts, plastic parts, medical equipment and precision sheet metals; sealing of minute parts; fine spot welding; high-speed seam welding; thick plate welding; etc.




TECHNICAL SPECIFICATIONS


TECHNICAL SELUII ICATION					
MODEL	ML-6920 A	ML-6930 A	ML-6940 A	ML-6950 A	
Maximum rated output	2000 W	3000 W	4000 W	5000 W	
Maximum peak power	2000 W	3000 W	4000 W	5000 W	
Output mode repeat	Standard: 0.1 - 500.0 msec. (0.1 msec. incremental) Switch to: 0.05 - 50.00 msec. (0.05 msec. incremental)				
Output mode cw	0.01 - 100.00 sec. (0.01 sec. incremental) 1 - 10000 sec. (1 sec. incremental)				
Pulse repetition rate	1 - 5000 pps				
Modulation	1 - 5000 Hz (sine wave, triangle wave, rectangular wave)				
Wavelength	1070 - 1080 nm				
Positioning guide light	Built-in red-colored visual laser (Class 2M)				
Output stability	+/- 2% or below @maximum rated output				
Optics	Optical fiber / Dual time sharing (optional)				
Delivery fibers	200 or 300 micron fiber cores Connectors QBH both input and output side Standard lengths 10 and 30 meters. Other fiber core diameters, connector types and fiber lengths available upon request				
Number of schedule	256				
Measurement	Measure and display power (W)				
Total counter	9 digits				
Ld time counter	7 digits				
Process time counter	7 digits				
Power consumption (including cooling power consumption (14.7 Kw)	Max. 24.7 kW	Max. 29.7 kW	Max. 30.7 kW	Max. 44.7 kW Cooling	
Cooling	Water cooled				
Pump source	Laser Diode				
Operating temperature	10 - 40 °C				

WEIGHT & DIMENSIONS

Weight (including control unit)	720 kg	760 kg	790 kg	900 kg	
Dimensions HxWxD	1775 mm x 2050 mm x 1081 mm				


DRAWINGS










Rear view






Main unit (1 to 2 deliveries)










Chiller cooler (LC 170.01-A.3.5/6)





Lindberghstrasse 1 • DE-82178 Puchheim, Germany T: +49 (0) 89 83 94 030 • Fax : +49 (0) 89 839403 68 infode@amadamiyachi.eu • www.amadamiyachieurope.com ISO 9001 Certified Company

EUROPE

Amada Mivachi Europe BV Helmond, The Netherlands T: +31 (0) 492 542 225 infonl@amadamiyachi.eu

Amada Miyachi Europe Kft. Budapest, Hungary T: +36 1 431 9927 infohu@amadamiyachi.eu

Amada Miyachi Europe Derby, United Kingdom T: +44 (0) 1332 361 238 infouk@amadamiyachi.eu Amada Miyachi Europe Saint Germain en Laye, France T: +33 (0) 139 046 430 infofr@amadamiyachi.eu

Amada Miyachi Europe Torino, Italy T: +39 011 223 83 16 infoit@amadamiyachi.eu

Amada Miyachi Europe Prague-West, Czech Republic T: +420 251 512 157 infocz@amadamiyachi.eu

AMERICAS

Amada Miyachi America Inc. Monrovia, CA, USA T: +1-626-303-5676 info@amadamiyachi.com

Amada Miyachi do Brasil Ltda.

Sao Paulo, Brasil T: +55-11-4193-1187 antonio.ruiz@miyachi.com

ASIA Amada Miyachi Co., Ltd. Noda, Japan T: +81-4-7125-6177 sales@miyachi.com

Amada Miyachi Shanghai, Co., Ltd. Shanghai, China T: +86-21-6448-6000 zqzhang@msc.miyachi.com

4/4

Amada Miyachi Korea Co., Ltd.

Gyeonggi-do, Korea T: +82-31-8015-6810 dykim@mkc.miyachi.com

MIYACHI |

UNITEK

Amada Miyachi Taiwan Co., Ltd. Taipei, Taiwan R.O.C. T: 886-2-2397-4778 keigaku@miyachi.com Amada Mivachi (Thailand) Co., Ltd. Samutorakarn, Thailand

MIYACHI

PECO

T: +66-2751-9337-8 info@mtl.miyachi.com

Amada Mivachi India Pvt., Ltd. Bangalore, Karnataka info@miyachiindia.com

MIYACHI

Amada Miyachi Vietnam Co., Ltd. Ho Chi Minh City, Vietnam T: +84-8-3771-7972







All data, images and text are subject to change at any time. Amada Miyachi Europe GmbH reserves the right to change, modify, delete and add technical specifications and product details at any time without prior notification. © 2015 Amada Miyachi Europe GmbH.