

## Straight Side D-Frame Single Crank Presses, DX1-Series

- Standard 1/7000 bed and slide deflection
- Hydraulic overload protection(HOLP)
- Pneumatically driven Wet clutch
- Link motion drive feature option available
- Flywheel drive FD version available with 8-point slide gibbing and high performance dry type air clutch and brake to meet 200 spm precision stamping

### 闭式D型单点曲柄驱动压力机

- 标配1/7000的机身(底座、滑块)变形率
- 标配液压过负荷保护装置(HOLP)
- 标配气动湿式离合器
- 选配多连杆传动机构
- 可选配飞轮直驱FD高速版, 配合8面滑块导轨及干式高性能刹车器实现200SPM精密冲压。



MODEL			DX1-800				DX1-1100				DX1-1600					DX1-2000				
Type			L	S1	S2	FD	L	S1	S2	FD	L1	L2	S1	S2	FD	L1	L2	S1	S2	FD
Capacity	能力	kN	800				1100				1600					2000				
Rating Point	能力发生点	mm	5	3.2		1.6	5	3.2		2.0	6		3.2		2.3	6		4.5		2.3
Stroke Length	行程长	mm	150	100	60	50	180	110	70	50	200	250	130	80	50	200	250	160	90	50
Stroke per Minute	行程数	SPM	40-75	55-110	75-150	100-220	30-60	50-110	65-135	100-200	25-50		40-80	55-110	100-200	25-45		35-70	45-90	100-200
Die Height (SDAU)	最大模高	mm	320	250		230	350	300		250	400		350		300	450		400		350
Max. Die Upper Weight	最大上模重量	Kg	500			200	650			250	750			300	950				400	
Slide Adjustment	滑块调整量	mm	80				80				100					110				
Bolster Area (LRxFR)	台面面积 (左右×前后)	mm	900 x 600	900 x 460	800 x 500	1000 x 680	1000 x 520				1150 x 760		1150 x 600			1250 x 840		1250 x 680		
Bolster Thickness	台面厚度	mm	120				120				150					170				
Slide Area (LRxFR)	滑块板面积 (左右×前后)	mm	700 x 460			600 x 460	800 x 520			700 x 520	900 x 580			800 x 580	1000 x 650				900 x 650	
Slide Plate Thickness	滑块底板厚度	mm	70				80				80					85				
Side Opening	侧向开口尺寸	mm	450x250			350x250	500x300			400x250	600x350			450x300	600x350				450x300	
Main Motor	VFD 主马达 变频调速	kWxP	7.5 x 4		11 x 4		7.5 x 4		11 x 4		11 x 4		15 x 4		15 x 4		18.5 x 4			
Machine Weight (Estimate)	整机重量 (预估)		8500				11500				17000					25000				

MODEL			DX1-2500				DX1-3150					
Type			L1	L2	S1	S2	L1	L2	S1	S2		
Capacity	能力	kN	2500				3150					
Rating Point	能力发生点	mm	6.5		4.5		7		4.5			
Stroke Length	行程长	mm	200	250	160	90	250	300	160	90		
Stroke per Minute	行程数	SPM	20-40		30-60		40-80	20-40		30-60		45-75
Die Height (SDAU)	最大模高	mm	450		400		450		400			
Max. Die Upper Weight	最大上模重量	Kg	1300				1400					
Slide Adjustment	滑块调整量	mm	120				120					
Bolster Area (LRxFR)	台面面积 (左右×前后)	mm	1250 x 840	1250 x 680	1250 x 840	1250 x 680	1250 x 840	1250 x 680				
Bolster Thickness	台面厚度	mm	180				180					
Slide Area (LRxFR)	滑块板面积 (左右×前后)	mm	1000 x 700				1000 x 700					
Slide Plate Thickness	滑块底板厚度	mm	85				85					
Side Opening	侧向开口尺寸	mm	770x400				770x400					
Main Motor	VFD 主马达 变频调速	kWxP	15 x 4		18.5 x 4		18.5 x 4		22 x 4			
Machine Weight (Estimate)	整机重量 (预估)		28000				32000					

