

DISTRIBUTORS OF

STRAPPING, SEALS. BUCKLES, TOOLS AND ACCESSORIES

FOR THE PACKAGING INDUSTRY





BOTTES

Metal Buckle

Non Slip Wire Buckle

(Quantity per Bag 1000) 13, 16, 19mm



Knurled Metal Wire Buckle



(Quantity per Bag 1000) 13, 16, 19mm

(Quantity per Bag 500)

Circular Wire Buckle

(Quantity per Bag 500) 19mm



Wire Tie



(Quantity per Roll 1000) packed in bags of 3000, 5000 or 10,000



Metal Seal

Serrated Open Gripper Seal for PET Strapping



(Quantity per Bag 1000) 12, 16mm

Open Seal for Plastic Strapping



UP 12 (12 width and 25 / 32mm length) **UP16** (16 width and 25mm length) **UP19** (19 width and 25mm length) (Quantity per Bag 2000)

Overlap or Closed Seal for Steel Strapping



(Quantity per Bag 2000) 13, 16, 19mm **Overlap Heavy Duty Seals**

(Quantity per Bag 1000) 19, 25, 32mm

Open Seal for Steel Strapping



(Quantity per Bag 2000) 10, 13, 16, 19mm **Open Heavy Duty Seals**

(Quantity per Bag 1000) 25, 32mm

Corner Seal 90°Steel



(Quantity per Bag 500) 32mm

Buckle Seal Stainless Steel (Galvanized)



(Quantity per Bag 100) Stainless Steel 10,13,16,19mm

(Quantity per Bag 2000) Galvanised Buckle 10,13,16,19mm

Heavy Duty Stainless Steel Buckle



(Quantity per Bag 100) Stainless Steel 10,13,16,19mm

Plastic Edge / Labels / Buckle

Carton Plastic Edge Protectors



Protect the edges of your carton and prevents the straps from slipping o.

- 19mm Corner Protector
- 32mm Corner Protector



Plastic / Metal Lables



- 64 x 125mm Plastic Lables - 64 x 125mm Metal Lables

Non-Corrosive Poly/Plastic Buckle





BoxesOmline

Strapping

Steel Strapping

- Oscillated





Oscillated Steel Strapping Special High Tension band painted, or gun blue and waxed steel strapping.

Steel Strapping - Ribbon Wound



Ribbon Wound Steel Strapping - Blue or Black painted and waxed steel strapping, this strapping diers from standard bright steel strapping, not only for its higher tensile strength but also for its better elongation.

PET Strapping

- Polyester



PET Strapping Polyester has a higher tensile strength than P/P (Polypropylene) strapping and its characteristics are long life, resistant to ultra violet light and weatherproof.

One of the great advantages is the high elasticity allowing the strap to remain tense even if the package shrinks after being strapped.

Polypropylene Strapping



Polypropylene strapping has many applications on manual and automatic machines. This strapping can even be used in the food industry, for bricks or newspapers.

Polywoven



Polywoven Strapping is made from high tensile polyester textile bres woven into a very exible and user friendly retensionable product. It is resistant to all weather conditions and UV light. It has a high linear system and capacity to absorb shocks during transport. It is suitable to be used from the lightest application to the lashing of loads.

Stretch Film - Cast Pallet Wrap



Available in dierent sizes and thickness



Heavy Duty Aluminum Tesnioner V391



Heavy Duty Aluminum Tesnioner with oilless bearings in handle and base. For 1/2" ~ 3/4" cord strapping.

Can be used on Flat surfaces

Light Weight Tensioner

VQ220



Light Weight Tensioner with oilless bearings in handle and base. For 1/2" $\sim 3/4$ " PP & PET strapping.

Can be used on Flat surfaces

Tensioner

V119



Heavy Duty Tensioner for plastic strapping with oilless bearings in handle and base. For 3/8" $\sim 3/4$ " cord strapping.

Can be used on Flat surfaces

Heavy Duty Tensioner

V112



Heavy Duty Tensioner with copper bushings in handle and bearings in base for plastic strapping. For 3/8" $\sim 3/4$ " plastic strapping.

Can be used on Flat surfaces

PET / Woven Strapping Tensioner V268



Strapping Tensioner with an extended nose section, designed to tighten 12m to 19mm PET and Polywoven/ Cord strapping. Specically for use with 12mm, 16, and 19mm wire buckles.

Can be used on Flat or Round surfaces

Heavy Duty Tensioner

V330



Heavy Duty Tensioner for Plastic Strapping with oilless bearings in handle and base. For 1/2" $\sim 3/4$ " PP & PET strapping.

Can be used on Flat surfaces



Pusher Bar Tensioner

V210



Rack-Type Pusher Bar Tensioner capable of adjusting straps ranging in widths from 10-13mm 0.38 to 0.6mm Steel Strapping. Ideal for Circular Applications.

Can be used on Flat or Round surfaces

Rack Pusher Tensioner

V227



Rack Pusher Tensioner with nose funciton for Strap Gauge Range (0.6 to 0.78mm)
Strap width range (16mm to 32mm)
Use with closed seal or wing seal.

Can be used on Flat or Round surfaces

Tensile Feed- Wheel Tensioner V350

Steel Strapping



Heavy Duty High Tensile Feed-wheel Tensioner with stronger and longer handle. For 3/4" $\sim 1-1/4$ " x 0.035" steel strapping. 8350 / 1400.

Can be used on Flat surfaces

HD Pusher Feedwheel Tensioner

V-249

Steel Strapping



Heavy Duty 3/4" ~ 1-1/4" x 0.6 ~ 1.2mm max. Steel strapping. Use with closed seal or wing seal when applying steel straps.

Can be used on Flat or Round surfaces

HD High Feedwheel Tensioner V296



Heavy Duty High Tensile Feedwheel Tensioner for steel strapping 3/8" ~ 3/4" x 0.035". Good for at packages.

Can be used on Flat

HD Feedwheel Tensioner

VP-1620



Heavy Duty Feedwheel Push Tensioner

Steel Strap Tensioner. Round Application Strap Gauge Range (0.6 to 0.78mm) Strap width range (16mm to 32mm)

Can be used on Flat or Round surfaces

HD Feedwheel Tensioner - Flat VIP-1400

Steel Strapping



Heavy Duty Feedwheel Tensioner

Strap Gauge Range (0.63 to 0.8mm) Strap width range (19mm to 32mm)

Can be used on Flat surfaces

Giant & Heavy Duty Tensioner V450



Tensioner, Heavy Duty Windlass, for use with PP PET and Polyvoven strappingcation Flat Surfaces, For Strapping Width 1 1/2 In, For Use With Heavy Duty Strapping, Requires Heavy Duty Application

Can be used on Flat surfaces

Heavy Duty Combination Tool VE1024



Heavy Duty Combination Tool. Tensioning, sealing and cutting tool for polyester PET/PP Combination Strapping tool. Size 12mm & 16mm

Can be used on Flat surfaces

Steel Strapping Rack-Type Tensioner V225



Hand Operated Manual RACK TYPE Strapping Tensioner with pusher nose section (with built in cutter), designed to tighten 9m to 19mm Mild Steel strapping around both at and circular objects.

Can be used on Flat or Round surfaces

Stainless Steel Tensioner

V260



Drop forged banding tool with built-in cutter for stainless steel bands 3/8" ~ 3/4" x 0.03" max. Essential parts are heat-treated.

Can be used on Flat or Round surfaces

Combination Tensioner

V1604



Combination tool (tensioning, sealing and cutting all in one) for PP strapping (12.5 - 1.6mm) 16mmPP/PET. Use with CP04 seals.

Can be used on Flat surfaces



Strapping Sealer

Plastic Strapping Sealers

V5004



High quality long handle (17") PET strapping sealer. All metal parts are heat-treated. For 5/8 PET strapping. Use with CP34 gripper seal.

PP Strapping Sealer

V3004



PP strapping sealer. Whole tool is heat-treated. For 13,16,19mm PP stapping. Use with CP04 / CP14 seal. Handle length 13".

Steel Strapping Sealer

V3203



Industrial Steel Strapping Sealer with double notches. Long handle, All metal parts are heat-treated.

C3203 for 3/8" steel straps C3204 for 1/2" steel straps C3205 for 5/8" steel straps C3206 for 3/4" steel straps

Crimpers Double Notcher

V3160



Crimpers Double Notcher Steel Stapping sealer

19mm x 0.9 Steel Strapping C3166 - 25mm x 0.9 Steel Strapping

C3180 - 32mm x 0.9 Steel Strapping

Table Top Heat Sealers

V100



Table Top Heat Sealer with plug-in timer, aluminum body, and sturdy plastic upper lever to give a lightly operating. Voltage(V): 110 / 220 / 240 Power(W): 260 Max. sealing(mm): 200 x 2 Heating time(Sec.): 0-1.5

H/D Rack Tensioner

V1932



Heavy Duty Rack Tensioner capable of tensioning straps ranging in widths from 16-32mm width and 0.5 to 0.9mm thickness Steel Strapping. Ideal for Circular Applications.

Can be used on Flat or Round surfaces



HD Plastic Strapping Dispenser



Mobile PP/Polywoven & PET Mobile strap dispenser for plastic band with seal tray and adjustable inner core diameter.

HD Steel Strapping Dispensor




Mobile Steel strap dispencer with seal tray for ribbon wound strapping. For strap widths from 10 to 32mm and also for oscillated wound strapping.

HD Strapping Dispenser



Mobile Strap Dispencer for plastic band with seal tray and adjustable inner core diameter.

HD Plastic Strapping Dispensor



Heavy Duty Strap Dispencer for plastic band with seal tray and adjustable inner core diameter.

Heavy Duty Steel Strap Cutter V-305



Heavy Duty Steel Strap Cutter SAE 4140 high carbon steel drop forged heavy duty steel strapping cutter for straps up to 2" x 0.05". 24" Handles

Aviation Tin Snips-s VAE6150



Cuts Straight or Wide Curves left to right in light stock Drop forged AISI-6150 chrome vanadium steel blades with induction hardened serrated edges. Cuts up to 1.2mm cold rolled steel or 0.7mm

Ratchet Tie-Down - Truck Tie-Downs



Constructed of durable polyester web, this handy and reliable Ratchet Tie-down / Truck Tie-down can secure and protect large loads.

(Tie Down Straps are also available with out the Ratchet)

Heavy Duty Steel Strap Cutter V201



Heavy Duty Steel Strap Cutter

Best selling carbon steel drop forged cutter with wide blades and yellow PVE grips.
For steel strapping 3/8" ~ 1-1/4" x 0.035".

Heavy Duty Bolt Cutters Chrome-Vanadium



Bolt Cutters Chrome-Vanadium steel forged jaws. Precision steel tube handles with PVC Grips.

Wire Puller



Fast secure sealing of heavy bags & sacks. Ideal for bundling rods, hessian sacks & heavy duty polyethylene bags. Easy to use twisting tool used with preformed wire ties. Quickly twists & tightens ties around metal & plastics



Hand Pallet Wrap Dispenser



Hand Pallet Wrap Dispenser - Pallet wrap Im is an easy and eective way to wrap and secure loads to a pallet regardless of shape or size. It will prevent dust or moisture contamination and ensures that goods stay on the pallet during transit.

Horizontal Paper Cutter Stand

VD100



Horizontal paper cutter with serrated blade to cut paper and lm. For roll diameter up to 9". For 24" working width.

Horizontal Paper Cutter

VD100



Horizontal paper cutter - "Serrated blade optional" to cut paper and Im. For roll diameter up to 9". For 24" working width.

Tape Dispenser

V276





Piercing the tape while applying the tape. Leaving a unique trace to your tape and the package it seals. It is a simple and cost eective way to reveal evidence if anyone attempt to open your package.

Blades for Cutting

Rotary Blade







- Rhombic Blade for form, foil, bubble wrap, thin PVC plastic sheet, and Im.
- Rotary Blade for paper and corrugated wrap.

Carton Stapler

VT103



Heavy duty Carton staplerFor 35mm wide x 15mm leg staples.

Bag Neck Sealer

12mm Metal Bag Neck Sealer





Metal desktop brand Bag Neck Sealer.

This sturdy dispenser is designed to manually dispense 12mm tape around the neck of a bag. Ideal for packing fruit and vegetables. Perfect for use with 50m and 100m rolls. Strong metal construction with rubber feet base.

PRODUCT SPECIFICATION

Width: 12mm

Type: Bag Neck Sealer

12mm Stainless Steel Bag Neck Sealer

V606STK



Metal desktop Bag Neck Sealer.

This STAINLESS STEEL dispenser is designed to manually dispense 12mm tape around the neck of a bag. Ideal for pack houses with high level hygiene requirements. For packing fruit and vegetables.

Perfect for use with 50m and 100m rolls.

Strong metal construction with rubber feet base.

PRODUCT SPECIFICATION

Width: 12mm

Type: Bag Neck Sealer Stainless Steel

24mm Heavy Duty Metal Bag Neck Sealer

V808K



Metal desktop brand Bag Neck Sealer.

This HEAVY DUTY dispenser is designed to manually dispense 24mm tape around the neck of a bag. Ideal for thicker or larger bags packing fruit and vegetables. Perfect for use with 50m and 100m rolls. Strong metal construction with rubber feet base.

PRODUCT SPECIFICATION

Width: 24mm

Type: Bag Neck Sealer Heavy Duty



Strapping Machine

Flat Strapping Tool - VT-POLI16HT

High Quality Pneumatic Sealless Plastic Strapping Tools

Strong and consinstent welding system.

Regulate the max tension with a clutch.

Precise adjustments for welding and tensioning are easily accessible.

Single-handed push-button operation.

Short and small base plate.

Very high tension speed.

Light, Friendly and easy to use.

Narrow width.

Strap Quality PP-PET

Joint Type Friction weld seal

Package Type Flat / Round (Min diameter 700mm /2

Strap Width 16-19 mm / 5/8" - 3/4" Strap Thickness 0,8-1,27 mm./.031" - .050" Tensione Max. 5000 N - 1100 Lbs

Max tension speed arround 6 mt/min - 20ft/min

Air pressure From 5.5 upto 6.5 bar max / 78-92 PSI Air Consumption 12 l/s tension 14l/s weiding / 29 cuft/min

Weight arround 5.3 kgs / 11,6 lbs



Tensioning and sealing of a straps
Band widths of 10-16mm and 16-19mm

The strapping device can be set to dierent band strengths.

In addition, tension sealing time are adjusted through the digital box.

Strap Quality: PP+ PET
Material: PP + PET
Bandwidth: 10 to 16 mm
Band strengths: 0.5 to 1.0 mm

Max Tension: 2000N. Gripping pace. 9 Mt / min. Weight with battery: 3.8 kg

Standard Battery: 12 V DC 2.0Ah Ni-CD

ngths. In the digital box.

Pneumatic Tensioner for Steel Strap

For Flat and Round Surfaces - Seal Required - 714 Kg Tension Uses standard and or high tensile steel strap from $\frac{3}{4}$ " to 1 $\frac{1}{4}$ Strap thickness from 0.8mm up to 1.2mm thick. Lightweight

Strap quality: Standard / High Tensile

Package type: Round / Flat Strap width: 19-25-32 mm Strap Thickness 0.8 - 1.2 mm

Strap Thickness 0.8 - 0.9 mm (High Tensile)

Max. Tension 9000 N / 918 Kg Max. Tension Speed 5.2 m/min

Air Pressure 6/7 bar
Air Consumption 18 lt/sec
Weight 4 kg / 8.82 lbs



Fully Automatic Strapper - Model VXS-108

We are renowned for bringing to the clients Fully Automatic Strapping Machine that is highly appreciated for longer service life and superior utility.

Highly durable range of Automatic Strapping Machine using high grade materials.

•The tension level can be adjusted as per requirement with maximum tension upto 90 kgs.

- ·Easy loading or unloading application
- Completely automated
- •Efficient performance
- •Light-weight
- Power Supply 3.-115V. 50Hz
- Arch Size W850xH600mm
- Strap Tension Max 90 kgs.
- Strap Width 9.12,15,19mm
- Dimension (mm) 910 (L)x 590 (W)x 730(H)
- Strapping Speed 2.4 sec/strap
- Min. Package Size L200xW200xH30mm
- Max. Package Size Any Size
- Weight 230 Kgs



Statpack Strapper - Model VXS-306

Statpack PP (Polypropylene) Strapping is an economical strapping material due to its lightweight and versatility.

By nature, PP strapping is very flexible and simplifies the job of strapping by its ability to mould contours of odd-shaped or irregular shaped packages.

Statpack PP Strapping can be applied to variety of sites and packaged goods, such as books & magazines, cardboard boxes, postal parcels and other goods bundled package.

- Machine Tension
- Strap Width
- Strapping Speed
5 - 50Kgs
5 - 15mm
1.5Sec. / Strap

- Dimension (mm) 895 (L)x 565 (W)x 740(H)

- Weight 230 Kgs

- Power Supply 100, 110, 220, 230, 240v.

50/60Hz 1-Phase

- Power Consumption 0.4Kw

