



AR-flex Flexible beaded cavity tubing

Ø 4.0 cm - 15.0 cm

MSL cavity tubing type **AR-flex** is folded spiral-seam tubing with a right-handed spiral and reinforcement beading of approximately 3.0 mm. **AR-flex** tubes are made of coiled banding 0.2 mm to 0.4 mm thick. Other thicknesses are available on request.

MSL cavity tubing is watertight so that no cement paste can later trickle into it during concreting or vibrating.

MSL cavity tubing type AR-flex is extremely rugged but can easily be bent into virtually any angle by contrast with the standard AR type. AR-flex is available from stock in 5 m lengths. Tailored and longer tubing is available on request.

Material: cold rolled zinced or black sheet metal depending on availability.

ATTENTION smallest bend radius 1.5 diameter



	Tubing inner diameter (cm)	4,0	5,0	6,0	6,5	7,0	8,0	9,0	10,0	12,0	13,5	15,0
AR- flex	Beading height, approximate (mm)	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0	3,0
пех	Weight, approximate (kg/rm)	0,37	0,47	0,55	0,60	0,65	0,73	0,80	0,90	1,05	1,16	1,32
ARD	Cover, steel, rigid, no nailing edge				Х		Х		Х	Х	Х	Х
ARDN	Cover, steel, loose, with nailing edge				Х		Х		Х		Х	Х
ARDK	Cover, plastic, loose, no nailing edge	Х	Х	Х		Х	Х	Х	Х	Х	Х	Х
ARDKN	Cover, plastic, loose, with nailing edge	Х	Х	Х	Х	Х	Х		Х		Х	Х

AR-flex Pos.	Quantity	Ø cm	Length m	Cov Type	ver Quantity
				ARD	

	Telephone	- Fax	
Text for invitation of tenders: Floring Make: MSL Manufacture pcs			flex.

Calculation

Shipping address:

Material: black/zinced. Beading height 3.0 mm Diameter: D = _

MIST.

Mathieu Schalungssysteme und Lufttechnische Komponenten GmbH INDUSTRIESTRASSE D-66625 SÖTERN Fon +49 (0) 6852 / 884-0 Fax +49 (0) 6852 / 884-10 www.msl-bauartikel.de e-mail: zentrale@msl-bauartikel.de Marketing and sales:

Length: L =

Subject to technical changes.

