

## LEVELING

## **Water Level 25**



## **SPECIFICATIONS**

Dimensions Unit:

> 6.35 in. H x 3.6 in. W x 1.37 in. D (161 mm x 91 mm x 35 mm)

Hose:

5/16 in. (8 mm) interior diameter.

25 ft. (7.6 m) length.

NOTE: hose extension kit available

1.53 lbs. (694 g) with hose Battery Type 9-V alkaline (not included)

**Estimated Battery Life** 

Weight

Up to 60 hours of continuous use (depending on battery type)

Position

Typically within 1/16 in. (2 mm)

Accuracy

Operating Temperature

20°F to 120° (-7°C to 49°C)

Storage Temperature

-20°F to 150° (-29°C to 66°C)

**Humidity:** 

80% (non-condensing)

Water

Splash and water resistant,

Resistance

not waterproof

## **Electronic Water Level with** 25-Foot Hose

Now one person can quickly and easily

locate precise level over long distances,

even out of sight and around corners up to 100 feet (30 m) away with additional hose.

We updated traditional water levels with modern electronics to ensure a new grade of accuracy. The WL 25 streamlines difficult layout tasks into simple one-man operations.

While you may have a good eye, precision can't be approximated. Use the WL 25 electronic water level to install decks, fences, chair rail, drop ceilings, and more.

- Allows one person to accurately level around corners and out of sight of the electronic control unit
- A consistent, high degree of accuracy regardless of distance from electronic unit
- Sound from the loud (95 db), continuous signal indicates level, even at long distances
- A loud pulsed tone sounds when above level
- Unit blinks and beeps to remind users that unit is on to prevent forgetting to turn it off-a true battery saver
- 25-foot hose included
- Additional hose available, sold separately



©2009 Zircon Corporation • C/N 1869 03/09