



### INNOVATION DRIVEN BY PASSION AND KNOWLEGDE ABOUT DREDGING





# DISCOVER THE ADVANTAGES

## AMPHIBIOUS EXCAVATOR WITH DOP PUMP

The machines are delivered all over the world. The equipment is made of high quality as a result that excavators are safe, durable and highly reliable. The WK 220, 250 and 300 NG-5 excavators can be combined with the right DOP pump.

WK 220 NG-5 WK 250 NG-5 WK 300 NG-5

	WK ZZO Na )	WK Z)O Ka )	With Joo Ha J
Upper structure	Doosan DX 225 LC-5 Standard semi long reach	Doosan DX 225 LC-5	Doosan DX 300 LC-5
Reach	13.0 M	13.5 - 14.0 M	14.0 - 15.0 M
Dimensions pontoon	10.00 x 2.00 x 1.50 M (lxwxh)	11.00 x 2.00 x 1.50 M (lxwxh)	11.00 x 2.00 x 1.92 M (lxwxh)
ADDITIONAL PONTOONS	AP 220 NG-5	AP 250 NG-5	AP 300 NG-5
Length spudpoles	6,00 M	6,00 M	6,00 M
Inclusive	Hydraulic spud poles	Hydraulic spud poles	Hydraulic spud poles
DOP PUMP			
Type  Max. power at shaft	Damen DOP 150   1,100 KG Damen DOP 200   1,360 KG Damen DOP 150   80 kW Damen DOP 200   120 kW	Damen DOP 150   1,100 KG Damen DOP 200   1,360 KG Damen DOP 150   80 kW Damen DOP 200   120 kW	Damen DOP 150   1,100 KG Damen DOP 200   1,360 KG Damen DOP 250   2,425 KG Damen DOP 150   80 kW Damen DOP 200   120 kW Damen DOP 200   195 kW
Max. mixture capacity	D150   600 M <sup>3</sup> /hr D200   800 M <sup>3</sup> /hr	D150   600 M³/hr D200   800 M³/hr	D150   600 M³/hr D200   800 M³/hr D250   1,250 M³/hr
Optional suction head	Auger Waterjet Cutter head	Auger Waterjet Cutter head	Auger Waterjet Cutter head
Cutter drive Max. power at shaft	D150 13 kW   D200 17 kW	D150 13 kW   D200 17 kW	D150 13 kW   D200 17 kW D250 28 kW
POWERPACK			

YES

NO with DOP 150

YES with DOP 200 and 250

YES

Necessary

With pump mounted



# Waterking BV

Phone

+ 31 (0)592 - 55 95 36

Website

www.waterking.nl

**Email** 

sales@waterking.nl

## Post address

PO Box 1, 9480 AA Vries The Netherlands

### **Address**

Mercuriusweg 22, 9482 WL Tynaarlo The Netherlands

