

## VERTIwrap Machine

Pro S180L



### Features

Twin type vertical packaging machine (based on VERTIwrap S100L), Vertical packaging machine, Emerson PLC, Eview (Taiwan) touch screen operator interface, automatic program set-up, mark sensor registration control, quick change former assembly, servo motor (PANASONIC) sealing unit, servo motor (PANASONIC) film pulling, double pulling possible, bag size: L(100-300) xW(80-240) (single pulling), up to 180 pcs./min., stainless steel, 380V/8KW, 6bar, 0.6m<sup>3</sup>/min., L2510xW1450xH1480mm, 1200/1300kg.

### Beschreibung

Vertikale Twin-Verpackungsmaschine (auf Basis der VERTIwrap S100L), Emerson PLC, Eview (Taiwan) Touchscreen-Bedienmonitor, automatisches Programm-Setup, Markierungssensor, Schnell-Wechsel-Form-Einheit, Schweißeinheit mit Servomotor, Servomotor (PANASONIC) für den Folientransport, Doppeltransport möglich, Beutelgröße: L(100-300)xW(80-240) (Single-Pulling), bis zu 180 stk./min., Edelstahl, 380V/8KW, 6bar, 0,6m<sup>3</sup>/min., L2510xW1450xH1480mm, 1200/1300kg.

### Product examples



### Bag Type (standard)



### Bag Type (optional)



### Specifications | Spezifikationen

Machine Type	VERTIwrap Machine Pro S180L
Article No.	C-GB-VW507-V-S180L
Bag Dimensions*	L(100-300)xW(80-240) mm
Packaging Speed*	0-180 pcs/min.
Power / Air*	380V / 8.0KW / 0.6m <sup>3</sup> / 6bar
Dimensions / Weight*	L2510xW1450xH1480 mm / 1200kg
Film material*	BOPP/PE, laminated films, etc.

\*There may be deviations from these specifications. Please feel free to contact us. Also ask for film specifications. / Es kann zu Abweichungen von diesen Angaben kommen. Bitte sprechen Sie uns an. Erfragen Sie auch die Folien-Spezifikationen.