

HPW-DUST

HIGH PRESSURE DUST SUPPRESSION SYSTEM







HPW-DUST

		HPW DUST 200	HPW DUST 200 DOUBLE DUST	HPW DUST 220 DOUBLE DUST	HPW DUST 180 DOUBLE DUST	HPW DUST 130 DOUBLE DUST
OUTPUT CHARACTERISTICS						
Output flow max.	l / min (U.S. gpm)	30 (7.9)	30 (7.9)	50 (13.2)	90 (23.75)	180 (47.5)
Pressure max.	bar (psi)	140 (2031)	140 (2031)	130 (1885)	140 (2031)	140 (2031)
Nozzle	pcs	4	2	4	4	4
High power nozzle	pcs	-	2	2	2	2
HYDRAULIC POWER REQUIREMENTS						
Flow max.	l / min (U.S. gpm)	40 (10.6)	40 (10.6)	70 (18.49)	115 (30.36)	140 (36.96)
Pressure max.	bar (psi)	160 (2321)	160 (2321)	160 (2321)	160 (2321)	160 (2321)
OVERALL PUMP DIMENSIONS						
Length	mm (in)	160 (6.3)	160 (6.3)	170 (6.7)	240 (9.4)	175 (6.9)
Width	mm (in)	245 (9.6)	245 (9.6)	280 (11.0)	330 (13.0)	400 (15.7)
Height	mm (in)	165 (6.5)	165 (6.5)	185 (7.2)	175 (6.9)	270 (10.6)
Weight	kg (lbs)	8 (17.6)	8 (17.6)	18 (39.6)	28 (61.7)	35 (77.2)
DESCRIPTION						
Application	Mobile crushers, crushing plants, mobile screeners, breakers, drilling rigs, loaders, dumpers, demolition machinery, etc.					
Standard supply includes HPW pump, hydraulic priority control valve, high pressure dust suppression nozzles, washing pistol with 10m pressure hose. Number of nozzles can be increased. Visit our website www.dynaset.com for detailed information.						

