

DESIGNED with plant-based plastic material Helping to reduce petroleum consumption EASY MEASUREMENT — by Anyone, Anytime, Anywhere



Environmental Radiation Monitor



DETECTOR



HORIBA

A RAILER

MEASURING the presence of environmental radiation around us

The HORIBA Radi:

Able to measure the environmental radiation (gamma rays) in our daily lives starting from **0.001** µSv/h

EUZZER COWER

Every day, wherever we go, we are exposed to minute amounts of environmental radiation.*

This environmental radiation is emitted continuously, day and night, from various objects and substances in the natural world and our living environment. Most environmental radiation consists of three types: alpha rays (α), beta rays (β) and gamma rays (γ). HORIBA's handy PA-1000 "Radi" environmental radiation monitor makes it easy for non-specialists to measure even minute levels of gamma rays.

* Environmental radiation, also known as natural radiation, includes radiation emitted from space, soil, stones, the ground and the air, as well as from manmade objects such as concrete and buildings

High performance detection with a CsI (TI) scintillator

Radiation measurement is displayed in large LCD display.

Unit: microsieverts per hour (uSv/h)

Sievert (Sv): a radiation unit used to quantify the effect of radiation on the human body.

Starts measurement.

lightweight.

Uses two AA batteries.

Automatic power off function after 3 hours.

Splash-resistant construction

with confidence even if there

(JIS water resistance protection

grade IPX4) The Radi can be used

are water droplets on the surface.

Handy unit is both compact and

Battery life 50 hours or more (when

manganese dry cell batteries are used)

The Radi can measure radiation levels ranging from normal natural radiation to levels 100 to 200 times that intensity.

Even non-specialists will find it easy to accurately measure radiation of 0.001 - 9.999 µSv/h.

Types of radiation

- Alpha rays (g): Alpha rays are streams of positively charged particles made up of two neutrons and two protons (helium nucleus). In the natural world, alpha rays are given off by radium 226. In air, the particles cannot travel more than a few centimeters.
- Beta rays (β): Beta rays are streams of electrons. In air, the particles can travel several dozen centimeters in a zigzag pattern.
- Gamma rays (γ): Gamma rays, the most penetrating type of radiation, are electromagnetic waves. They can pass through the human body. X-rays that are used in X-ray machines are also electromagnetic waves.

Radiation units

- Becquerel (Bq): The becquerel (Bq) is the unit of radioactivity. The radioactivity of a substance measured in becquerels is the number of its nuclei that decay each second.
- Gray (Gy) and Sievert (Sv): These units express the effect of radiation. The gray expresses the amount of radioactive energy received, while the sievert expresses the effect on a human being. Normally the gray and the sievert are used to express quantities per hour; the units are Gy/h and Sv/h, respectively.

The International Commission on Radiological Protection (ICRP) has recommended exposure to the general public of no more than 1 mSv per year to manmade radiation (not including natural radiation). This does not include exposure from medical checkups (such as X-rays). (1 mSv = 1000 µSv)

HORIBA continues contributing to the preservation of the global environment through analysis and measuring technology.



[Selectable]

Audible beep when radiation is detected.

Specifications

-			
Detection method	Scintillation		
Type of radiation measured	Gamma rays (γ)		
Sensitivity	Min. 1000 counts per minute (1000 cpm) for 1 µSv/h		
Relative error of indication	±10%		
Indicator value variation	Max. 0.1 coefficient of variation		
Energy range	More than 150 keV		
Energy properties	0.5 - 3* (150 keV - 1250 keV)		
Effective measurement range and display	0.001 - 9.999 μSv/h		
	4-digit digital display		
	(count value converted into µSv/h)		
Sampling time	60 seconds		
Display interval	60-second integrated value (moving average) displayed every 10 seconds		
External dimensions	68 (W) × 28 (D) × 121 (H) mm [Inch size : 2.7 (W) × 1.1 (D) × 4.8 (H)]		
Weight (without batteries)	Max. 175 g (6.2 oz)		
Accessories	Instruction manual, two AA dry cell batteries, neck strap		

* Relative sensitivity with 1 as the sensitivity to cesium 137 (137Cs) (662 keV).

Note: This unit is designed only to measure the quantity of radiation at the measurement location. It does not determine the safety or danger posed by that quantity of radiation.

Please read the operation manual before using this product to assure safe and proper handling of the product.

• The contents of this catalog are subject to change without prior notice, and without any subsequent liability to this company.

- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.
- •All brand names, product names and service names in this catalog are trademarks or registered trademarks of their respective companies.

http://www.horiba.com e-mail: info@horiba.co.jp

●HORIBA, Ltd. Head Office 2 Miyanohigashi, Kisshoin Minami-ku, Kyoto, Japan Phone: 81 (75) 313-8123 Fax: 81 (75) 321-5725	Tokyo Sales Office 1-7-8 Higashi-Kanda Chiyoda-ku, Tokyo, Japan Phone: 81 (3) 3861-8231 Fax: 81 (3) 3861-8259	●HORIBA Trading (Shangh Shanghai Office Room 1701, United Plaza, 1468 Nanjing Rd. West, Shanghai, 200040, China Phone: 86 (21) 6289-6060 Fax: 86 (21) 6289-5553	hai) Co., Ltd. Beijing Office Room 1801, SK Tower, Tower 1 No.6Jia, Jianguomenwai Ave., Chaoyang District, Beijing, 100022 China Phone: 86 (10) 8567-9966 Fax: 86 (10) 8567-9066	HORIBA Instruments Pte L Head Office 10 Ubi Crescent #05-11/12, Ubi Techpark Singapore 408564 Phone: 65 6745-8300 Fax: 65 6745-8155	td Hanoi Office Unit 10, 4 Floor, CMC tower, Dich Vong Hau Ward, Cau Giay district, Hanoi, Vietnam Phone: 84 (4) 3795-8552 Fax: 84 (4) 3795-8553
•HORIBA KOREA LTD. 112-6 Sogong-Dong Choong-Ku, Seoul, Korea Phone: 82 (2) 753-7911 Fax: 82 (2) 756-4972	 HORIBA India Private Lim Delhi Office 246. Okhla Industrial Estate, Phase 3 New Delhi-110020 Phone: 91 (11) 4669-5001 Fax: 91 (11) 4669-5010 	ited Pune Office 502, Purushottam Plaza, Baner Road, Baner, Pune - 411045 INDIA Phone: 91 (20) 2729-1121 Fax: 91 (20) 2729-1121	HORIBA Instruments Incorporated Irvine Facility 17671 Armstrong Avenue Irvine, CA 92614, U.S.A. Phone: 1 (949) 250-4811 Fax: 1 (949) 250-0924	HORIBA Instruments Limit Kyoto Close Summerhouse Road Moulton Park, Northampton NN3 6FL, U.K. Phone: 44 (1604) 542500 Fax: 44 (1604) 542699	ted
HORIBA GmbH Kaplanstrasse 5 A-3430 Tulln, Austria Phone: 43 (2272) 65225 Fax: 43 (2272) 65230	HORIBA Czechia Organizachi slozka Praha Petrohradska 13 CZ-101 00 Praha 10, Czech Republic Phone: 420 (2) 717-464-80 Fax: 420 (2) 717-470-64	HORIBA Europe GmbH - Head Office Hans-Mess-Str.6 D-61440 Oberursel/Ts. Germany Phone: 49 (6172) 1396-0 Fax: 49 (6172) 137385	Leichlingen Facility Julius-kronenberg Strasse D-42799 Leichlingen Germany Phone: 49 (2175) 8978-0 Fax: 49 (2175) 8978-50	HORIBA France 12, Avenue des Tropiques 91955 LES ULIS France Phone: 33 (1) 69-29-96-23 Fax: 33 (1) 69-29-95-77	
Bulletin:HRE-3923A					Printed in Japan TH-K(SK)53

Explore the future

Automotive Test Systems | Process & Environmental | Medical | Semiconductor | Scientific

