



Connect | Condition | Acquire

→ Key Features

- Highly portable, standalone acquisition unit
- 16/24-bit ADC, >114dB SNR, 5-256kHz Sample Rates
- Multiple Gigabit Ethernet Connectivity
- High Performance Intel Core i5/7 processor
- Multiple Signal Conditioning Options
- Multi-unit Synchronisation (GPS, IRIG, LVDS, IEEE-1588)







--- Introduction

The Eagle³² is a 32 channel data acquisition system designed to provide a world class, highly portable solution for dynamic data recording and real time monitoring.

The Eagle³² features multiple gigabit Ethernet connections, allowing remote control from remote laptops or PCs, as well as data streaming for monitoring / archiving. The system can also operate autonomously, acquiring vast amounts of data using the built-in high performance CPU and substantial solid state disk drive.

The Eagle³² is intended for rack-mounted or laboratory use where vibration and environmental factors are not extreme (see the HGL Hummingbird for ruggedized acquisition systems).

The Eagle³² has proven itself worldwide in numerous small, medium and large scale test cells with Aero, Industrial and Marine Gas Turbine manufacturers.

The Eagle³² can be provided in a number of chassis sizes (1U, 2U & 3U) depending on conditioning requirements. All of the form factors provide the same HGL standard interfaces (Ethernet, 12V power, & LVDS Sync) and all are completely compatible with all other Eagle, Hummingbird and Dragonfly family modules.

Eagle³² units can be supplied with and without integral CPUs and Storage as indicated by an FP designator (i.e. Eagle³² = with CPU, Eagle^{32FP} = No CPU Front Panel Version).

Within some limits, conditioning can be mixed within a single unit on 8 channel boundaries.

The Eagle³² Family provides the ultimate in flexible 32 channel rack-mounted Data Acquisition modules / systems.



3U Chassis

Available in both Integrated CPU and FP versions Supports all Conditioning card types **2U Chassis** Available in both Integrated CPU and FP versions Supports all Conditioning card types (excluding 15-pin variants) **1U Chassis** Available in both FP versions only Supports all Conditioning card types (excluding FE-1408-APC and 15-pin variants) **3U Eagle^{PC}**

Provides CPU & Storage (6-12TByte) for FP versions of Eagle³²

All variants fit standard 19" Racks and are 9" (23cm) deep.





- Hardware Overview

Eagle³²



data

http://www.hgl-dynamics.com

data stored on the SSD drive.







Software Overview

HGL Dynamics provides multiple software platforms for Hummingbird Acquisition systems; these range from low level Network APIs, Windows[®] DLL, LabVIEW[™] Drivers, Single Instrument Applications (Apps), and full Measurement System software. This flexibility allows users to choose the best platform for their particular applications and / or increases the utilisation of the hardware for multiple uses.

Network API

All HGL Dynamics hardware modules are Ethernet connected to each other and their host PC(s); a fully documented Programmer's API is available for integrators / customers who wish to access the modules at this level or need to integrate the modules with a non-Windows operating system.

Microsoft Windows DLL

HGL provides (as standard) a Windows DLL with every Hummingbird Acquisition System; for Microsoft Windows users this provides a simpler method to access all the functions of the hardware.



LabVIEW[™] Driver

HGL can provide a LabVIEW[™] driver for the Hummingbird Acquisition System; this driver allows full access to the functionality of the hardware, and is available for the Microsoft Windows Operating System.

Single Instrument Apps

HGL has developed a number of Single Instrument Apps, primarily for its Firefly system. These apps can be operated on a Hummingbird and Laptop / PC system equally well. The Apps are intended to provide a family of simple, easy to use applications which turn the Hummingbird into a single instrument, examples include:

- FFT Analyser
- Oscilloscope
- Chart Recorder
- Rotating Machinery Analyser
- Trim Balance
- Power Dip & Rise (requires isolation amplifier hardware)



Full Measurement System Software

For the past 15 years, HGL has providing a fully integrated, modular, network distributed Dynamics Measurement System; this software is intended for wide variety of applications and for systems ranging from small portable units to large multi-site systems with hundreds or thousands of channels. The System comprises four main parts, Acquisition, Monitoring, Analysis and Data Management, and is focused on providing robust, flexible, fixed or mobile operation with ease of use as a primary consideration.







Software Overview

Data Acquisition - Hawk

HGL's Hawk acquisition software provides everything a user needs to configure, calibrate and acquire data from the acquisition hardware. Full control and feedback of the system is provided by the Hawk GUI Client application; this provides an intuitive instrument-like interface that allows even novice users to operate large channel count systems, even from remote locations.





Real-Time Monitoring - Hawkeye

Hawkeye allows one or more users to monitor the signals being acquired in realtime (<0.1s latency).

Fully customisable displays such as FFTs, Waterfalls, Oscilloscopes, Numerical, Speed and Tracked-orders, Phase, Bode, Orbit, nth Octave etc, provide a rich monitoring environment.

Hawkeye also provides Time, Frequency, Order and Phase domain alarming facilities for all channels simultaneously, with support for many different alarms types per channel. Hawkeye is also client / server based with the 'thin' Hawkeye Client allowing local or remote monitoring (performance dependent on network infrastructure).

Analysis - Aurora

Aurora provides an in-depth analysis tool for acquired data; this is usually required post-test, but can be operated simultaneously with testing if useful. Post-test analysis can pinpoint areas of interest / problems to be further investigated, and for this purpose Aurora provides a range of client / server based tools to analyse, investigate, mine, summarise and report on acquired data.

Multiple users can use Aurora simultaneously, and in common with HGL software portfolio access is via a network connected thin-client (Aurora Client) application, thus allowing both local and (potentially widely) remote users to access data simply and efficiently.





Data Storage & Archiving - Hercules

Prolonged or large-scale data acquisition generates a lot of data, 10's and 100's of TBytes are not unusual for large enterprises. Data is expensive to collect and the functionality to efficiently store and retrieve legacy data is essential for in-service investigations, product development etc.

HGL's Hercules software provides an integrated, low-cost, yet highly scalable and safe data management solution for any sized data acquisition operation. The key to the system's success is support for virtually any common media type (SD cards, HDD/SSDs, LTO tapes etc.) combined with a unique database architecture providing simple, yet highly efficient data storage information, and a client/server architecture which allows data to be managed across multiple remote sites from a single intuitive Graphical User Interface.







---- Condition --

Signal Conditioning

The Hummingbord³² module can be fitted with a wide range of internal signal conditioning cards which further extend the Hummingbird's capabilities. Single or multiple conditioning functions are possible depending on card choice.



HGL has designed a set of conditioning cards that fulfil most industry standard

requirements. However more cards are developed as clients' requirements change. The signal conditioning options currently available for the Hummingbird³² module are:

- FE-1404-DFY: Voltage, IEPE, and Proximeter Probe conditioning card
- FE-1407-IA: 4-Channel High voltage isolation amplifier
- FE-1408-APC All-purpose conditioning card including Voltage, IEPE, Bridge, Dynamic Strain, and Charge. On-board sensor health check and buffered dual analogue outputs.
- FE-1409-DFY: Voltage and IEPE (ICP) multi-range conditioning card. On board sensor health check and buffered analogue outputs
- FE-1410-BRG / DYN Voltage & Bridge Only and IEPE & Dynamic Strain only variants of FE-1408-APC card
- FE-1411-MIC Voltage, IEPE & 200V Excited Microphone Conditioning
- HGL-HiZ: AC/DC Voltage only conditioning with gain

| | Voltage | | IEPE | Bridge | Dynamic | Charge | Temperature | Proxii | |
|-------------|--------------|--------------|--------------|------------------------|-----------------------|--------------|-------------------|--------------|--------------|
| Cond. Card | AC | DC | Accel / Mic | Strain (¼, ½, full) | Strain (SG, Press) | Accel | Therm. & PT100 | meter Probe | Speed |
| FE-1404-DFY | \checkmark | \checkmark | ✓ | | | | | \checkmark | ~ |
| FE-1407-IA | ~ | ~ | | | | | | | ~ |
| FE-1408-APC | \checkmark | \checkmark | \checkmark | \checkmark | \checkmark | \checkmark | ✓# | | \checkmark |
| FE-1409-DFY | \checkmark | \checkmark | \checkmark | | | | | | \checkmark |
| FE-1410-BRG | \checkmark | \checkmark | | \checkmark | | \checkmark | ✓# | | \checkmark |
| FE-1410-DYN | ~ | | ~ | | ~ | \checkmark | | | ✓ |
| FE-1411-MIC | \checkmark | \checkmark | ✓ | | | \checkmark | | | \checkmark |
| HGL-HiZ | \checkmark | \checkmark | | | | | | | \checkmark |







Specification

General

Dimensions (W x H x D): Weight: Supply Voltage: 435 x 200mm x 1-3U 11.0 kg (typical) 110-250V ac 50/60Hz (FP Models 12 V DC) 30-60 W (typical)

Computer

Processors:Intel® Core ™ i7 Dual Core 2.4GHz (typ.)Memory:8.0 GB (typ.)Storage:1 TB SSD (typ.)O/S:Windows® 7 Professional

Power:

Input Configuration (with standard 1408 signal conditioning card)

32

Input Channels: ADC Type: Quantization: Input Ranges: DC Offset: Input Coupling: Input Impedance: SNR: Anti-aliasing: Sample Rate: Frequency Response: Dynamic Range: Inter-Channel Δ Phase: Crosstalk:

Distortion: DC Linearity: Drift:

Sigma-Delta 24-bit / 16-bit* ±10 V to ±0.1 V in 1, 2, 5 steps* ±0.15 mV AC, DC * >100 kΩ >120 dB <-100 dB 5 - 256 kHz * DC to >100 kHz ±0.017 dB 140 dBFS / √Hz, 114 dB (broadband) < 20 nS (< 0.36° @ 10 kHz output signal) < 100 dB @ 5 kHz, < 95 dB @ 10 kHz, < 87 dB @ 20 kHz, < 82 dB @ 40 kHz, < 70 dB @ 100 kHz < -80 dB, 0 to 80 kHz < 0.01%



*Software configurable parameter

< 25 ppm/°C (with no correction applied)

Synchronisation

LVDS: LVDS (max distance) IRIG A/B: GPS: 10 ns per unit 200 m [#] (node to node) ±100 ns ± 50 ns

[#]If longer distances are require please contact HGL

Environmental

Operating Temp.: -25 to 70°C Storage Temp: -40 to 85°C Relative Humidity: < 90% RH non condensing

Other Inputs (using any standard input)

IRIG-A and IRIG-B Audio Voice Annotation Tachometer







Training

Training

HGL Dynamics offers a wide variety of training workshops and courses. Workshops are conducted at one of our global offices or at the client's site by our training team, all of whom have many years' of industry experience and knowledge.

Typical training courses include: Vibration Fundamentals, Signal Processing, Rotating Machinery, Advanced use of HGL Software and Analysing Large Datasets.



Information

About HGL Dynamics

HGL Dynamics is a world-leading supplier of services and high specification equipment for the integrated capture, monitoring, analysis, storage and management of high bandwidth data.

Purchasing & Availability

The HGL Dynamics Hummingbird³² Data Acquisition Module is now available for purchase or lease. Please contact one of our HGL Dynamics offices below for further information or to request a quote.

---- UK & International ----

HGL Dynamics Ltd Hamilton Barr House Bridge Mews Godalming GU7 1HZ UK

Tel +44 1483 415177

--- North America ----

HGL Dynamics Inc 2461 Directors Row Suite J Indianapolis IN 46241 USA

Tel +1 317 782 3500

---- France ----

HGL Dynamics France 25 Rue du Mont Olivet 78500 Sartrouville France

Tel +33 1 75 93 80 20

--- South Korea ----

HGL Dynamics South Korea 768 Posvill Officetel Gumi-dong, Bundang-gu Seongnam-si Gyeonggi-do Korea 483-861

Tel +82 109 052 2638



Company registered in England No. 3844513

info@hgl-dynamics.com

(♥)≞_`

FS72209