
IK-72T

All Position Gas Cutting



Portable, Automatic All-Position Gas Cutting Machine Cuts Flat to Multi Plane Surfaces

The KOIKE IK-72T cuts various types of steel including channel, curved plate and angled steel members. Made of aluminum alloy, the IK-72T is lightweight and easy to use. A graduated bevel collar is provided for beveling. Simply adjust the scale for precise bevel angle.

Features & Benefits

- All Purpose Oxy Fuel Cutting
 Bevel cut or straight cut in or out of position using 1, 2, or 3D rail.
- Permanent Magnet Track
 Secures track to plate; allows track to be used vertically.
- 1D, 60 in (1,500mm) Extendable Rail Aluminum rail; makes accurate straight cuts; extendable track allows cutting of longer parts.
- 2D 40 in (1,000mm)
 Extendable Flex Track
 Make straight cuts and curved plane cuts;
 extendable track allows cutting of longer

parts.

- 3D 40 in (1,000mm)
 Extendable Flex Track
 Makes straight cuts and twisted plane cuts; extendable track allows cutting of longer parts.
- Clutch Lever
 Releases side rollers to allow quick positioning of machine on rail.


Innovative Use of Materials for

- Precision Cutting
 Hard rubber compound used on the rails allows curving through 2 or 3 panels; flexible steel tubing is set along rail centers and prevents uneven cutting.
- High Quality Tips
 KOIKE's superior design Series 100 torch
 tips are included to ensure fast, smooth
 cuts.
- Optional Snap Valve
 One-touch On/Off gas valve



SPECIFICATIONS		
Minimum Curved Line Length	60 in (2000mm) radius 3D rail 98 in (2500mm) radius 2D rail	
Cutting Thickness	½ - 2 in (5-50mm)	
Cutting Speed	6-28 in/min (150-700mm/min)	
Speed Control	Triac variable resistor	
Drive Method	Rack and pinion	
Bevel Angle	0-45°	
Power Source	AC 120V/220V	
Weight	8.8 lb (4.0kg)	
Cutting Tip - 102 for Acetylene, 106 for LPG	Koike 100 series	







Cutting a radius using a triple (3D) plane rail



Straight cutting on aluminum rail using a single (1D) plane rail

MODELS DESCRIPTION	
IK-72T (110V model) Includes: (1) IK-72T Machine Unit (1) Oxy-Fuel Torch (3) Cutting Tips 102 for Acetylene; 106 for LPG (1) Safety-Z Coupling Set	TBJA21002 Sizes 0, 1 & 2 7A3232260
IK-72T (220V model) Includes: (1) IK-72T Machine Unit (1) Oxy-Fuel Torch (3) Cutting Tips 102 for Acetylene; 106 for LPG (1) Safety-Z Coupling Set	TBJA24014 Sizes 0, 1 & 2 ZA3232260
Rail Section	(Choose from below)

RAILS AND SNAP VALVE OPTION		
1D Rail (straight plane) Vertical cutting is possible 60 in (1,500mm)	TBPJ64025	
2D Rail (double plane) 1D(up) + 1D(down) 40 in (1,000mm)	ZS31680	
3D Rail (triple plane) 1D(up) + 1D(down) + 1D(twist) 40 in (1,000mm)	TBPJ64026	
Snap Valve	SNAPVALVEI	

Cutting Precision

Koike's IK-72T unit is ideal for ship, vessel and tank/building repair. Proper rail selections ensures the highest precision. Double plane and triple plane curved rails are the choice for most precision cutting, but may not be best for straight cutting. The straight rail is ideal for this. Triple plane curved rail used for double plane cutting may also reduce linear precision.

For maximum magnet efficiency and reduction of rail movement, be sure to clean rusty plate before cutting. Do not cut heavily painted plate or use rail with dirty magnets. Avoid operating where vibration occurs. Cutting plate less than $\frac{1}{4}$ in (6mm) is not recommended. Be sure to use properly fitted magnets on the plate.



LIFETIME TORCH WARRANTY


* Against a sustained flashback when using a genuine Koike cutting tip (Damaged torch and genuine Koike cutting tip must be returned)



Bevel cutting

APPLICATIONS

Triple-plane curve cutting at the bow of a ship using triple-plane curved rail



Using a double-plane curved

Using a straight rail





P.O. Box 307, Arcade, New York 14009 Phone (585) 492-2400 Fax (585) 457-3517 **www.koike.com**

