

MODEL **KRI-10**

Impact Ratchet



FEATURE

- Impact clutch mechanism.
- 2.5 times faster. (As compared to Kuken ratchet wrench.)
Reduction of working hours.
- Reducing the reaction force after the screw sitting.

APPLICATIONS

- Fastening work of small dia bolt, nuts and screw below 10mm
- Disassembly work for oil pan, water pump and air conditioner of automobile.
- Fastening / loosing work of bolt at narrow space.

SPECIFICATIONS : (Performance figures are at 0.62 MPa(Pe) / 90 P.S.I. air pressure.)

Drive Size	9.5	mm	...	3/8	in
Capacity of Bolt Size	10	mm	...	3/8	in
Free Speed	500	r.p.m.			
Max Torque	30	Nm			
Weight (w/o socket)	0.65	kg	...	1.43	lbs
Length (w/o socket)	174	mm	...	6-7/8	in
Air Consumption	0.25	m ³ /min	...	8.9	c.f.m.
Hose Size	6.3	mm	...	1/4	in
Air Pressure	0.62	MPa	...	90	P.S.I.



KUKEN CO., LTD.

3-6-15 Nonoue, Habikino-shi, Osaka 583-0871, Japan
Tel : +81-72-953-3346 Fax : +81-72-953-0605

Web : www.kuken.co.jp/english E-mail : export1@kuken.co.jp



CAT NO. 260612-KRI10