

PRESSURE WASHERS

USING PRESSURE WASHING EQUIPMENT FROM THE PLATFORM OF A JLG® BOOM LIFT



Usage Guidelines

- The hose leading to the pressure washer gun should either be routed along the boom sections using clamps or guides, or run through the power track from the ground to the platform. The routing of the hose must not interfere with boom functions. JLG does not permit loose hoses or cables hanging freely from the platform to the ground.
- The platform load must not exceed the capacity of the lift in use at any time. The platform load includes material, personnel, tools, equipment and accessories. The weight of the pressure washer and the entire weight of the water supply hose in use, plus water, must be included when determining platform load.
- The reaction force of water leaving the pressure washer nozzle must not exceed 50% of the maximum allowable side force of the lift in use. The allowable side force is indicated on the capacity decal within the platform and/or in the appropriate Operation and Safety Manual.
- The overspray from the pressure washing must be accounted for when considering the Minimum Approach Distances (M.A.D.) to live electrical conductors.

All applicable safety procedures and precautions (country, local, employer, manufacturer, etc.) must be strictly followed, as outlined in the appropriate Operation and Safety Manual.

Operators should obtain any additional training required to properly operate the equipment from the boom lift.

The aerial work platforms being used must be current with Annual Machine Inspection requirements, with all noted discrepancies properly corrected. All decals/placards must be legible and properly installed (positioned) on the machine. The Operation and Safety Manual and other appropriate publications must be located within the designated manual storage compartment.

Contact JLG with any questions about using pressure washer equipment.
1-877-JLG-LIFT (1-877-554-5438)
productsafety@jlg.com

JLG Industries, Inc.

1 JLG Drive
McConnellsburg, PA 17233-9533
Telephone 717-485-5161
Toll-free in US 877-JLG-LIFT
Fax 717-485-6417
www.jlg.com

An Oshkosh Corporation Company

