

EVA50/FLASH EVC50/FLASH

zone 1

zone 2

Ex db IIC Gb Ex tb IIIC Db II2GD

T6
T 85°C



zone 21

zone 22

DIRECTIVE 2014/34/UE



LIGHTING FIXTURE
XENON FLASHING LAMP

SEGNALATORE LUMINOSO
LAMPADA XENON

IP66



Caratteristiche:	Segnalatore luminoso con lampada allo Xenon ad elevato rendimento, sono idonee per la segnalazione ostacoli per camini, ciminiere, fiaccole, campanili, palazzi, gru, ponti, torri radiotelevisive, piloni di teleferiche e linee elettriche, generatori eolici, antenne radar e telecomunicazioni e, nello specifico, per il mondo dell'industria petrolchimica e petrolifera. Certificata INERIS, bassi consumi e durata illimitata. Guarnizione O-RING in neoprene per protezione meccanica IP66. Connessione Direttamente al portalamпада L, N, Pe. Sez. max. 4mm2.
Features:	Lighting fixtures with long-life xenon bulb, are ideal for chimneys, towers, smokestacks, bell towers, buildings, cranes, bridges, radio/television masts, cable car and power line pylons, wind turbines, radar and telecommunication antennas and specifically for use in the petrochemical and oil industries. INERIS certificate, low consumption and high performance. Neoprene O-RING gasket for protection IP66. Connection Direct to lamp holder L, N, Pe. Max section 4mm2.
Materiali:	Lega di alluminio a basso contenuto di rame, viteria in acciaio inox, Vetro borosilicato resistente agli urti ed alle alte temperature sigillato nella ghiera in alluminio, gabbia in acciaio inox (se richiesta).
Materials:	Low copper content aluminium alloy, stainless steel hardware, Shock and temperature resistant borosilicate glass sealed with aluminium shade ring, stainless steel guard (on request).

EVA50/FLASH

EVC50/FLASH

EVA50+KIT/FLASH



Specifica tecnica / Technical specification

	EVA50 EVC50	SOLO EVC50 ONLY EVC50		EVA50 EVC50		
Tensione / Voltage	12-24 VAC/VDC	48 VAC	48 VDC	110 VAC	110VDC	230 VAC
Corrente / Rated current	300mA		40mA		20mA	
Temperatura / Working temperature	-20°C +60°C					
Frequenza / Frequency	50/60HZ					
Assorbimento medio / Power middle	2W		1,8W		4,5W	
Lamp power / Effective Intensity	6J 29Cd					
Flash-minuto / Flash-minut	75 (other to be defined)					
Servizio / Service	Continuo / Continuous					
Colore corpo / Color body	RED RAL 3000 / Other color on request					
Imbocchi / Cable entries	EVA50 1 x 3/4" - EVC50 2 x 3/4"					



COLORI GEMME: ROSSO - GIALLO - ARANCIO - VERDE - BLU - BIANCO
Signaling lamps: Red - yellow - orange - green - blue - white

